

# Eclipse II Extreme

**(480 VAC)**

**HF Fast/Opportunity Charger  
Industrial Battery Charger**



**SPEC SHEET: 1271 SPEC**

**INDEX: 030113**

**REPLACES: Original**

| Number Battery Cells | Model Number     | Max. AH Capacity in 8 hours | Maximum DC Output Amps | Phase | AC Input Amps at 480 VAC 60 Hertz-3 ph | Approx. Weight (lbs.) |
|----------------------|------------------|-----------------------------|------------------------|-------|--|-----------------------|
| 6,12,18              | 1200EC3-18TE**   | 1200                        | 480                    | 3     | 28.8                                   | 198                   |
| 6,12,18              | 1400EC3-18TE**   | 1400                        | 560                    | 3     | 33.6                                   | 198                   |
| 6,12,18              | 1575EC3-18TE**   | 1575                        | 630                    | 3     | 37.8                                   | 212                   |
| 6,12,18,24           | 850EC3-24TE      | 850                         | 340                    | 3     | 28                                     | 198                   |
| 6,12,18,24           | 1050EC3-24TE**   | 1050                        | 420                    | 3     | 33.6                                   | 198                   |
| 6,12,18,24           | 1175EC3-24TE**   | 1175                        | 470                    | 3     | 37.6                                   | 212                   |
| 6,12,18,24           | 1400EC3-24XE2*** | 1400                        | 560                    | 3     | 86                                     | 575                   |
| 6,12,18,24,36,40*    | 700EC3-40TE      | 700                         | 280                    | 3     | 37.4                                   | 198                   |

\* Control does not auto select between 36 and 40 cell.

\*\* Arcless disconnect and dual output cables REQUIRED. Also requires an SBX or Euro connector.

\*\*\* Arcless disconnect and 2 sets of dual output cables REQUIRED. Also requires SBX or Euro connectors.

**TE Triple Engine Overall Dimensions: 21.25" wide x 17" deep x 52" high**

**XE Dual Triple Engine Overall Dimensions: 32" wide x 36" deep x 79" high**



**TE Triple Engine Cabinet**



TROY, OHIO 45373, U.S.A.

PHONE: 800-367-2002